



TrackDock® from CSD Systems is part of the unique custom solutions range of products aimed at meeting the needs of specific customers.

The TrackDock system was originally developed to meet a specific customer requirement. It comprises frames and covers specifically designed for working on the railways.

KEY BENEFITS

- Designed and built on the principles of rapid assembly, portability and durability
- Heavy-duty 1000 gauge clear poly construction
- Long skirts to ensure good ground contact
- Translucent white poly SpeedDock entrance airlock
- Complete pack includes both covers and all necessary clips
- Lightweight but sturdy Aluminium folding frame on the TrackDock
- Galvanised steel frame for the SpeedDock

The TrackDock frame is purpose-built from heavy gauge Aluminium.

It is designed to span the railway track and is open at the bottom to allow direct access to the working area.

The legs fold under for ease of transportation and with the whole unit weighing less than 30Kg, it can easily be maneuvered into place by two workers.

Where time is particularly tight, such as night working on the Tube, the unit can be constructed complete with the polythene cover before being moved to the working area. It is then just a matter of minutes before asbestos (or other hazardous) removal can commence.

The SpeedDock Single Chamber airlock is designed to work as an entrance passage to the TrackDock. It is constructed from white translucent polythene for privacy and is suspended from a galvanised steel SpeedDock frame.

The unit comes complete with weighted welded-in entrance flap and all the clips necessary for installation.

In order to enable working in confined spaces, the unit measures 74cm by 74cm base and 1.88m height. We can also supply it in 100cm base by 2.00m height, if required.

The connection to the TrackDock is left uncut to avoid limiting the setup configuration.

TrackDock Cover Pack


The TrackDock Cover Pack contains just about everything you might need to set up the system. Comprising:

- 1 x TrackDock tent
- 1 x Single chamber SpeedDock airlock
- 1 x Set of SpeedClips for the SpeedDock

The frames for the TrackDock and SpeedDock chamber are available separately.

Specification

The TrackDock cover is fabricated from clear 1000 gauge (250µm) polythene. It is transparent enough to enable working with external light sources and the double welded seams are designed to withstand heavy use for prolonged periods. The cover is made to tightly fit the TrackDock frame. This enables rapid installation without the use of tape.



Frame folded for transportation

TrackDock®

CSD Systems Limited
Pantiles Chambers, 85 High Street, Tunbridge Wells, Kent TN1 1XP, UK
Phone +44 (0) 1892 614 366 Fax +44 (0) 1892 535 475
www.speeddock.com info@cspdsystems.co.uk